

QSG, IB, Power Cord, Remote Control, RC Battery, IR Extender, Mounting Kit, Extension Brackets

Yes

PANEL

Screen Size	88"
Panel Technology	IPS
Backlight Type	DLED
Brightness (typical)	700 cd/m2
Native Resolution	3840 x 1080 (32:9)
Contrast Ratio (typical)	1100:1
Dynamic Contrast Ratio	70000:1
Panel Life Time (Min.)	50.000 Hrs
Response Time (typical)	8 ms
Active Area (H x V)	2148mm (H) x 598mm (V)
Refresh Rate (ms)	60 Hz
Viewing Angle	178°
Color Value	10-bit(D), 1.07 B colours
Screen Treatment	3H
Haze Level	1%
H-Freq	135 KHz
Max. Pixel Freq.	74.25 MHz
Refresh Rate	60 Hz
Front Type	Ultra Narrow Bezel
Orientation	Landscape/Portrait
Operation Hours	24/7 PID Panel
Area of Usage	Indoor

MAINBOARD

Mainboard Model	MB135VS
-----------------	---------

MONITOR CONNECTIVITY

RGB Input	VGA(DE-15F)
RGB Output	N/A
Video Input	4xHDMI2.0, 1xDP1.2a, 2xUSB2.0, USB2.0(Internal)
Video Output	HDMI2.0, DP1.2a
Audio Input	Line In L/R
Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)
External Sensor	RJ12

MECHANICAL

Product Dimensions (WxDxH)	966 x 106 x 557 mm
Package Dimensions (WxDxH)	1050 x 178 x 718 mm
Product Weight	10.3 kg
Package Weight	13.65 kg
Vesa Mounting	200 x 200 mm - M6
Bezel Width	B:13 T:9 L/R:10 mm

ENVIRONMENTAL CONDITIONS

Operating Temperature	0°C to +40°C
Operating Humidity	10-90%

POWER

Power Supply	110 VAC - 240 VAC
Power Consumption (Typical)	TBD

POWER CONSUMPTION

Typical	TBD
Deep Standby	<0.5W

MECHANICAL FEATURES

Size	2161 mm (W) x 614mm (H) x 118mm (D)
Vesa Mounting Size	600 mm x 400 mm
Bezel Width	8 mm (R/L) - 15mm (T/B)

FEATURES

Main Features	*Joystick, Internal USB Cover, Detachable Power Cable, Carrying slot / handle"
Speaker	2 x 8 W2 x 12W

ACCESSORY

Standard	*QSG, IB, Power Cord, Remote Control, RC Battery, IR Extender, Mounting Kit, Extension Brackets"
----------	--

CERTIFICATION

EMC	YES
CB	YES